

EVERUN ER06 WHEEL LOADER 4WD



Standard Configuration-----

Standard Bucket, Yanmar 3TNV88-BSSY Engine(Euro3), Unclosed Cabin, Tipping Cabin, Hydrostatic Transmission System, Quick Hitch, Floating Function, Electric Joystick, Hydraulic-Pressure Checking System, 26*12-12 Tyres, Parallel Linkage System, Free Service Spare Parts.

Optional Configuration-----

Closed cabin, LED Light, E4 Lamp, Varta Anti-Freeze Battery, Extra Hydraulic Line, Yanmar 3TNV88-ESSY Engine(EPA4), Kohler 1603 Engine(EPA4)), Different Attachments.

Vehicle Parameter-----

Bucket capacity	0.26m ³	Overall height	2250mm
Loading capacity	600kg	Overall width	1200mm
Net weight	1700kg	Dumping reach	800mm
Lifting time	≤8.0s	Dumping height	1870mm
Max. turning angle	±35°	Working pressure	17MPa
Min. turning radius	2450mm	Wheel base	1340mm
Max. driving speed (I/II)	12 km/h	Breakout force	13KN
Oil flow	28L/min	Tyre	26*12-12
Min. Ground Clearance	220mm	Engine model	Yanmar 3TNV88-BSSY

Fuel consumption ration	252g/kWh	Engine power	19.6KW
Overall length (bucket on ground position)	3673mm	Rated speed	2200r/min
Lifting height (with bucket)	3086mm	Service brake	4 wheel hydraulic spread-shoed brake