

EVERUN ER08 WHEEL LOADER 4WD



Standard Configuration-----

Standard Bucket, Changchai 390 Engine, Torque Converter Transmission System, Rops & Fops Cabin, Quick hitch, Electric Joystick, Floating Function, Tipping Cabin, Adjustable Steering Wheel, Comfortable Seat, Cabin Heater, Backward Camera, Hydraulic-Pressure Checking System, Engine Heater, 31*15.5-15 Agricultural Tyres, Lock for Lifting and Steering Cylinder, Parallel Linkage System, Free Service Spare Parts.

Optional Configuration-----

Air Conditioner, Extra Hydraulic Line, LED Light, E4 Lamp, Varta Anti-Freeze Battery, 20.5/70-16 Tyres, 31*15.5-15 Turf Tyres, Tyre Chain, Three-Point Hitch, Loading Damper, Centralized Lubrication System, Loader Weighter, 5 Functions Electric Joystick, Kohler 1903TCR Engine(EPA4), Different Attachments.

Vehicle Parameter-----

Bucket capacity	0.48m ³	Overall height	2580mm
Loading capacity	800kg	Overall width	1570mm
Net weight	2700kg	Dumping reach	800mm
Lifting time	5s	Dumping height	2100mm
Max. turning angle	35°±1	Working pressure	17MPa

Min. turning radius	4600mm	Wheel base	2050mm
Max. driving speed (I/II)	7.8/23 km/h	Breakout force	22KN
Oil flow	50L/min	Tyre	31*15.5-15
Min. Ground Clearance	220mm	Engine model	Changchai 390 Engine
Fuel consumption ration	276g/kWh	Engine power	25KW
Overall length (bucket on ground position)	4550mm	Rated speed	2400r/min
Lifting height (with bucket)	3463mm	Service brake	4 wheel hydraulic spread-shoed brake