

EVERUN ER12 WHEEL LOADER 4WD



Standard Configuration-----

Standard Bucket, Xinchai 490 Engine(Euro 3 Engine), Torque Converter Transmission System, Rops & Fops Cabin, Quick hitch, Electric Joystick, Floating Function, Tipping Cabin, Adjustable Steering Wheel, Comfortable Seat, Cabin Heater, Backward Camera, Hydraulic-Pressure Checking System, 220V Engine Heater, 20.5/70-16 Agricultural Tyres, Lock for Lifting and Steering Cylinder, Parallel Linkage System, Free Service Spare Parts.

Optional Configuration-----

Air Conditioner, Extra Hydraulic Line, LED Light, E4 Lamp, Varta Anti-Freeze Battery, 31*15.5-15 Agricultural Tyres, 33*15.5-16.5 Turf Tyres, Tyre Chain, Three-Point Hitch, Loading Damper, Centralized Lubrication System, Loader Weighter, 5 Functions Electric Joystick, Kohler 1903TCR Engine(EPA4), Cummins QSF2.8 Engine(EPA4), Yanmar 4TNV94L Engine (Euro3), Different Attachments.

Vehicle Parameter-----

Bucket capacity	0.53m3	Overall height	2530mm
Loading capacity	1200kg	Overall width	1720mm
Net weight	3300kg	Dumping reach	940mm
Lifting time	7s	Dumping height	2547mm
Max. turning angle	35°±1	Working pressure	17MPa
Min. turning radius	5450mm	Wheel base	2265mm

Max. driving speed (I/II)	10/22 km/h	Breakout force	28KN
Oil flow	66L/min	Tyre	20.5/70-16
Min. Ground Clearance	240mm	Engine model	Xinchai 490
Fuel consumption ration	235g/kWh	Engine power	36.8kw
Overall length (bucket on ground position)	5049mm	Rated speed	2650r/min
Lifting height (with bucket)	3837mm	Service brake	4 wheel hydraulic spread-shoed brake