

EVERUN ER20 WHEEL LOADER 4WD



Vehicle Parameter-----

ENGINE

Model	XIChai4Dx21-72	Engine Type	In-line arrangement, water cooled four cycle diesel engine
Rated Power	55kw	Fuel Consumption Ratio	230g.kw.H
Rated speed	2400r/min		

TRANSMISSION SYSTEM

Type	Fixed spindle power shift	Shift gear oil pressure	1.2-1.5Mpa
Rated input speed	2500rpm		

BUCKET

Bucket capacity	1.0-1.2m ³	Bucket width	2100mm
Bucket type	Heavy-duty bolt on teeth	Rated load	2000kg

OPERATING SPECIFICATIONS

Steering system	Articulated frame with hydraulic power steering	Min Turning Radius	4600mm
------------------------	---	---------------------------	--------

Driving System	Hydraulic converter	Operating weight	5700kg(not attachments)	incl.
-----------------------	---------------------	-------------------------	-------------------------	-------

OVERALL DIMENSIONS

Overall length	5800mm	Overall Height	2750mm
Dumping Height	3100mm	Min. Base to Ground	350mm
Overall Width	2000mm		

BRAKING SYSTEM

Service Brake	Four-wheel hydraulic spread-shoed brake	Parking Brake	Hand operated
Tyre	16/70-20 or 23.5-16		