

EVERUN ER416H WHEEL LOADER 4WD



Standard Configuration-----

Standard Bucket, Hydrostatic Transmission System, Xinchai 3E22YG40 Engine(Euro IIIB), Quick Hitch, Floating Function, Electric Joystick, 130W Heater, 220V Engine Heater, Rops & Fops Cabin, Tipping Cabin, Luxury Cabin Inside, Backward Camera, Comfortable Seat, Adjustable Steering Wheel, Wheel-Reducer Axle, Hydraulic Brake, Lock for Lifting and Steering Cylinder, Hydraulic-Pressure Checking System, Parallel Linkage System, 23.5/70-16 Agricultural Tyres, Free Service Spare Parts.

Optional Configuration-----

Hydraulic Line, LED Light, E4 Lamp, Varta Anti-Freeze Battery, 315/80 R22.5 Snow Tyres, Tyre Chain, Air Conditioner, Loading Damper, Centralized Lubrication System, Loader Weighter, 12.8/80-18 Tyres, Bobcat Quick Hitch, Kohler 1903TCR(42KW, Tier4).

Attachments-----

Pallet Forks, 360 Degree Wooden Forks, Normal Wooden Forks, Grapple Bucket, Snow Bucket, Normal Snow Blade, Adjustable Pallet Forks, Sand Spreader, V Snow Blade, Food Blade, Sweeper with box, Europe Grapple Forks/Grass forks, Snow Blower, 4 in 1 Bucket, Bale Grab, Mixer Bucket, Auger, Snow bucket with Wings, Hydraulic JIB, High Tipping Bucket

Vehicle Parameter-----

Bucket capacity	0.64m ³	Steering System	Heavy-duty Articulated Oscillating
Bucket width	1850mm	Min. turning radius	3870mm
Bucket type	Heavy duty bolt-on teeth	Max. turning angle	40°
Loading capacity	1600kg	Driving System	Electric Control
Net weight	4700kg	Engine model	Xinchai 3E22YG40 (EUROIIIB Standard)
Overall length (bucket on ground position)	5344mm	Engine Type	In-line Arrangement, Water-cooled, Three-Cycle Diesel Engine
Overall Height (ground to cab top)	2517mm	Rated power	45KW
Dumping height	2466mm	Rated speed	2400r/min
Min. Ground Clearance	275mm	Fuel consumption ration	240g/kWh
Overall width	1820mm	Transmission system	Hydrostatic transmission
Parking brake	Hand operated	Driving pump pressure	400Bar
Service brake	Four wheel hydraulic spread-shoed brake	Tyre	23.5/70-16