

EVERUN ER1500F TELESCOPIC LOADER 4WD



Standard Configuration-----

Standard Bucket, Xichai 498BT Engine(EuroIII Engine), Rops & Fops Cabin, Electric Joystick, Quick Hitch, Adjustable Steering Wheel, Comfortable Seat, 130W Heater, Backward Camera, Engine Heater, Wheel-Reducer Axle, Disc Brake, 23.5/70-16 Agricultural Tyres, Blinking Lamp Without Key, Free Service Spare Parts.

Optional Configuration-----

E4 Lamp, LED Light, Trailer Ball, Multifunction Electric Joystick with 5 buttons, Multifunction Electric Joystick with 4 buttons, Rear Hydraulic Line, Loading Weighter, Centralized Lubrication, Extra Electric Line, Varta Anti-Freeze Battery, Loader Damper, Bobcat Quick Hitch, Euro Quick Hitch, Trima Quick Hitch, Extra Heater, Extra Oil Cooler, 8 Gears Shift, Air Seat (without air pump), Crane Valve, Rear Sand Spreader Oil Line + Left Joystick, 3 Point Hitch, Air Conditioner, Diesel Heater, Tyre Chains, Without Cabin with Roller Bar.

Optional Tires & Engines-----

14-17.5 Tubeless tires, 400/60-15.5 tires, 33*15.5-16.5 tires, Kohler 1903TCR Engine(Tier 4), Yanmar 4TNV94L Engine(Euro3), Cummins QSF2.8 Engine(Tier4), Yanmar 4TNE98-BQFLC Engine

Vehicle Parameters-----

ENGINE

Model	Xichai A498BT1	Rated speed	2400 r/pm
Engine Type	In-line arrangement, water cooled, four-cycle diesel engine	Fuel consumption ratio in Standard working condition	230g/kW.h
Rated power	37kW (50.32 HP)	Transmission system	Hydraulic converter + drive shaft + axles

BUCKET

Bucket type	Heavy duty bolt on teeth	Rated load	1500kg including attachment
Bucket width	1700mm	Bucket capacity	0.65m ³

OVERALL DIMENSIONS

Overall length (bucket on ground)	5037mm	Overall Height	2551mm
Overall Width	1850mm	Max. Lifting Height	4105mm

OPERATING

SPECIFICATIONS

Steering System	Articulated frame with hydraulic powersteering	Min. turning radius	4950mm
Driving System	Hydraulic converter, 4-wheel drive	Other	Quick coupling system; joystick, self-levering

BRAKE SYSTEM

Service Brake	Four wheel hydraulic spread-shoed brake	Parking Brake	Hand operated
----------------------	---	----------------------	---------------

TYRE

Model	23.5/70-16 Tyre	Width	340mm
Diameter	900mm		
Wheelbase	2140mm		

Track	1345mm
System Pressure	20MPa; Hydraulic output: 70L/min