

EVERUN ER2500F TELESCOPIC WHEEL LOADER 4WD



Standard Configuration-----

Standard Bucket, Xichai 4DX21-72 Engine, Torque Converter Transmission System, Rops & Fops Cabin, Electric Joystick, Quick Hitch, Tipping Cabin, Adjustable Steering Wheel, Comfortable Seat, Cabin Heater, Backward Camera, Hydraulic-Pressure Checking System, Engine Heater, Wheel-Reducer Axle, 16/70-20 Agricultural Tyres, Lock for Lifting and Steering Cylinder, Parallel Linkage System, Free Service Spare Parts.

Optional Configuration-----

Quick Hitch, Electric Joystick, Air Conditioner, LED Light, E4 Lamp, Varta Anti-Freeze Battery, Tyre Chain, Three-Point Hitch, Loading Damper, Hydraulic Joystick, Centralized Lubrication System, Loader Weighter, 5 Functions Electric Joystick, Different Attachments.

Vehicle Parameter-----

Bucket capacity	0.67m ³	Overall height	2736mm
Loading capacity	2500kg	Overall width	1870mm
Net weight	5900kg	Dumping reach	1012mm
Lifting time	7.2s	Dumping height	3848mm
Max. turning angle	31°	Working pressure	20MPa

Min. turning radius	5068mm	Max Tractive force	35KN
Max. driving speed (I/II)	22 km/h	Breakout force	25KN
Max Gradeability	20°	Tyre	16/70-20
Max Lifting Height	5413mm	Engine model	XICHAI 4DX21-72
Fuel consumption ratio	230g/kWh	Engine power	53KW
Overall length (bucket on ground position)	5631mm	Service brake	Air-on-oil, Caliper disk