

EVERUN ER425 WHEEL LOADER 4WD



Standard Configuration-----

Standard Bucket, Xichai 4DX22-96 Engine, Torque Converter Transmission System, Rops & Fops Cabin, Hydraulic Joystick, Floating Function, Tipping Cabin, Adjustable Steering Wheel, Comfortable Seat, Cabin Heater, Backward Camera, Hydraulic-Pressure Checking System, Engine Heater, Wheel-Reducer Axle, Air Brake, 16/70-20 Agricultural Tyres, Lock for Lifting and Steering Cylinder, Parallel Linkage System, Free Service Spare Parts.

Optional Configuration-----

Quick Hitch, Electric Joystick, Air Conditioner, Extra Hydraulic Line, LED Light, E4 Lamp, Varta Anti-Freeze Battery, Tyre Chain, Three-Point Hitch, Loading Damper, Centralized Lubrication System, Loader Weighter, 5 Functions Electric Joystick, Cummins QSF3.8 Engine(Euro3), Different Attachments.

Vehicle Parameter-----

Bucket capacity	0.67m3	Overall height	2737mm
Loading capacity	2500kg	Overall width	1970mm

Net weight	5900kg	Dumping reach	830mm
Lifting time	4.8s	Dumping height	3045mm
Max. turning angle	35°±1	Working pressure	18MPa
Min. turning radius	4974mm	Wheel base	2430mm
Max. driving speed (I/II)	5/15 km/h	Breakout force	55KN
Oil flow	92L/min	Tyre	16/70-20
Min. Ground Clearance	320mm	Engine model	XICHAI 4DX22-96
Fuel consumption ratio	220g/kWh	Engine power	70kw
Overall length (bucket on ground position)	5696mm	Rated speed	2400r/min
Lifting height (with bucket)	4501mm	Service brake	4 wheel hydraulic spread-shoed brake