

# EVERUN ERE45 EXCAVATOR



## Optional Attachments-----

300mm narrow bucket, 600mm bucket, 1200mm bucket, air conditioner, hammer, drill, change to steel track

## Vehicle Parameter-----

<b>Operating weight</b>	4000kg	<b>Digging bucket capacity</b>	0.16m <sup>3</sup>
<b>Engine</b>	YANMAR 4TNV88	<b>Hydraulic system work pressure</b>	21+4mPa
<b>Engine power</b>	33.1kW	<b>Slewing speed</b>	12.5rpm
<b>Travel speed</b>	2.5-4.5 (km/h)	<b>Bucket digging force</b>	23.1kn
<b>Gradeability</b>	<35°	<b>Arm digging force</b>	16.2kn
<b>Valve</b>	KYB, Japan	<b>Swing Motor type</b>	Axial-piston motor
<b>Swing motor</b>	KYB, Japan	<b>Brake</b>	Hydraulic oil released
<b>Parking Brake</b>	Hydraulic disc brake		

## MAIN DIMENSIONS

<b>Overall dimensions</b>	5560x1650x2560mm	<b>Min ground clearance</b>	290mm
---------------------------	------------------	-----------------------------	-------

<b>Track length on ground</b>	1750mm	<b>Track width</b>	300mm
-------------------------------	--------	--------------------	-------

## OPERATING RANGE

<b>Max Digging Depth</b>	3530mm	<b>Max dumping Height</b>	2400mm
--------------------------	--------	---------------------------	--------

<b>Max Digging height</b>	5310mm	<b>Max digging reach</b>	5740mm
---------------------------	--------	--------------------------	--------

<b>Max vertical digging depth</b>	2750mm
-----------------------------------	--------