

EVERUN EREL04 ELECTRIC WHEEL LOADER 4WD



Standard Configuration-----

Standard Bucket, Quick Hitch, Maintenance Free Batteries, Electric Joystick, LED Working Lights, 6.00-12 Tyres, Free Service Spare Parts.

Optional Configuration-----

Closed cabin, LED Light, E4 Lamp, Varta Anti-Freeze Battery, Extra Hydraulic Line, Yanmar 3TNV88-ESSY Engine(EPA4), Kohler 1603 Engine(EPA4)), Different Attachments.

Vehicle Parameter-----

PERFORMANCE

Bucket capacity	0.2m ³	Dumping reach	450mm
Lifting Height	2100mm	Dumping height	1350mm
Rated load	0.4t	Max Excavation Force	8kn
Max. turning angle	±28°	Max lifting weight	400kg
Max Grade ability	15	Swing degree of rear axle	3

DIMENSION & WEIGHT

Overall length (bucket on ground position)	2800mm	Overall Height	2070mm
Bucket width (overall width)	900	Min ground clearance	300mm
Wheel base	1387mm		
Net Weight	900kg		

BATTERY

Battery Model No.	6-EVF-100A	Rated Voltage	60V
No. of battery groups	5	Working Hours	4h
Rated capacity(3hr)	100Ah		

TRANSMISSION SYSTEM

Hydraulic System

Motor No.	HL-60	Voltage	60V
Power	1200W	Displacement	14 ml/r
Tyres			
Type	6.00-12	Working pressure	0.25 mpa
Qty	4		

STEERING SYSTEM

Type of Steering	Full Hydraulic	System Pressure	16 mpa
Hydraulic System	Steering System		
Type of Steering Pump	External Gear Pump	Steering Cylinder Bore	50mm
Qty	1 pc		

BRAKING SYSTEM

Service Brake	Drum Brake	Brake Drum	200mm
Parking Brake	Drum Brake		

Distribution Valve	Model DL 10 Type: Triple Valve System
---------------------------	---

Dumping Cylinder Bore

Ø50

Lifting Cylinder Bore

Ø50

OIL CAPACITY

Hydraulic Oil Tank

11L

Brake Fluid

0.8L